

Machinery

Machining centers

Takisawa TMM-250M1 (2x)	Max. dia 350 mm	Max. length 800 mm
DMG MORI CTX beta 800 TC (1x)	Max. dia 500 mm	Max. length 750 mm
DMG MORI CTX beta 1250 – 4A (1x)	Max. dia 340 mm	Max. length 1 135 mm
DMG MORI CTX beta 800 – 4A (1x)	Max. dia 340 mm	Max. length 735 mm
OKUMA MULTUS B750-W 3000 (1x)	Max. dia 1 050 mm	Max. length 3 000 mm
DMG 100U Duoblock (1x)	Max. dia 1 000 mm	Max. height 1 600 mm

Automation

ABB Robot (1x)	Type: IRB 2600	Protection: Standard	Max. load (static): 20 kg
FANUC Robot (1x)	Type: M-710iC/70	Protection: Standard	Max. load (static): 70 kg

Turning

DMG MORI CTX 310 Ecoline (1x)	Max. dia 200 mm	Max. length 400 mm
Kovosvit MAS KL 285 Y (3x)	Max. dia 285 mm	Max. length 550 mm
Kovosvit MAS KL 285 SY 1x)	Max. dia 285 mm	Max. length 550 mm
MORI SEIKI NLX 2000/500 – SY (2x)	Max. dia 350 mm	Max. length 510 mm
DMG MORI CTX Beta 1250 (2x)	Max. dia 410 mm	Max. length 1 235 mm
DMG MORI CTX Beta 800 (2x)	Max. dia 410 mm	Max. length 700 mm
Okuma LB3000MY (1x)	Max. dia 410 mm	Max. length 1 000 mm
Okuma LU300MY (1x)	Max. dia 370 mm	Max. length 1 000 mm
Kovosvit MAS SP 430 1100 (3x)	Max. dia 430 mm	Max. length 1 100 mm
Kovosvit MAS SP 430 2500 (1x)	Max. dia 430 mm	Max. length 2 500 mm
MORI SEIKI NZX – S1500/1000 (1x)	Max. dia 120 mm	Max. length 1 055 mm
TOS SUA80 CNC (1x)	Max. dia 840 mm	Max. length 5 000 mm
SPT32 CNC (7x)	Max. dia 320 mm	Max. length 1 500 mm
SPM16 CNC (1x)	Max. dia 160 mm	Max. length 500 mm
HARDINGE TALENT 6/52 (1x)	Max. dia 160 mm	Max. length 500 mm
Manual lathe SU18-SU80 (7x)	Max. dia 1 250 mm	Max. length 5 000 mm
MC SK8 CNC (1x)	Max. dia 800 mm	Max. height 700 mm

Milling

EMCO MMV 2000 (1x)	Max. table width 850 mm	Max. table length 2 400 mm
EMCO EmcoMill 1200 (1x)	Max. table width 610 mm	Max. table length 1 200 mm
Romi D800 (1x)	Max. table width 500 mm	Max. table length 914 mm
Vertical milling machines (2x)	Max. table width 400 mm	Max. table length 1 600 mm
Horizontal boring mills (2x)	Max. table width 1 800 mm	Max. table length 1 800 mm
DMG MORI DMU 50 Ecoline (1x)	XYZ: 500x450x400 mm	B axis +5°- 110°, C axis 360°

Grinding

TOS BUB 50B CNC/1500 MULTI (1x)	Max. dia 500 mm	Max. length 1 500 mm
TOS BUA 25B NC/1250 PRACTIC (1x)	Max. dia 250 mm	Max. length 1 250 mm
TOS BUC 63 (1x)	Max. dia 630 mm	Max. length 4 000 mm
TOS BUC 40 (1x)	Max. dia 500 mm	Max. length 3000 mm
BLOHM ORBIT 48 CNC (1x)	Max. width 400 mm	Max. length 800 mm

Thread rolling

ORT 120RP NC (1x)	Max. dia 210 mm	Rolling pressure 120 t
ORT RP90 NC (1x)	Max. dia 160 mm	Rolling pressure 90 t
PROFIROLL PR 60e RPS (1x)	Dia 10-120 mm	Rolling pressure 60 t

Deep drilling

TIBO E40-2-1500 (1x)	Dia. 5÷42mm	Max. length 2 500 mm
-----------------------------	-------------	----------------------

EDM - wire cutting

Fanuc alfa C600iC (1x)	Max. table width 600 mm	Max. table length 400 mm
-------------------------------	-------------------------	--------------------------